

Data sheet LED pendent luminaire PSLU100

- Light up with: SMD LED
- System power: 44W / 57W
- Colour rendering index: CRI >80
- Power supply: with power supply
- Connection voltage: AC 230 V
- Energy efficiency: A++ - A
- Protection class: 1
- Test certificates: CE
- Material: extruded aluminium
- Colours: white, black, anodized aluminium



Technical data for PSLU100 44W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSLU100-1200SW10	PSLU100-1200WW10	PSLU100-1200NW10
Art.No. black	PSLU100-1200SW20	PSLU100-1200WW20	PSLU100-1200NW20
Art.No. anodized aluminium	PSLU100-1200SW70	PSLU100-1200WW70	PSLU100-1200NW70
System power	44W		
Luminous flux (lm)	3237	3237	3553
System efficiency (lm/W)	74	74	81
UGR	19		
Version: Light distribution	direct 65% / indirect 35%		
Dimensions L x B x H	1230 x 45 x 100 mm		

Technical data for PSLU100 57W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSLU100-1500SW10	PSLU100-1500WW10	PSLU100-1500NW10
Art.No. black	PSLU100-1500W20	PSLU100-1500WW20	PSLU100NW20
Art.No. anodized aluminium	PSLU100-1500SW70	PSLU100-1500WW70	PSLU100-1500NW70
System power	57W		
Luminous flux (lm)	4193	4193	4603
System efficiency (lm/W)	74	74	81
UGR	19		
Version: Light distribution	direct 65% / indirect 35%		
Dimensions L x B x H	1530 x 45 x 100 mm		